Auto Splicer 自動接料機

1. 電源 Power supplier (v) ---------- 3phase/220V/380V
2. 機器尺寸 Machine dimension (mm) ---------- 2120L x 1300W x 2070H mm
3. 氣源 Air supplier (KG/CM²) ---------- 6KG/CM²
4. 機器重量 Machine weight (kg) ---------- about 700kg
5. 總功率Total Power (kw) ---------- 1.4kw

本公司基於研究改進之必要，因此保有外觀尺寸規格等修改之權利。
All specification and design characteristics shown in this catalogue are subject to change without notice.



各種標籤套入法

Various label insertion methods operated by XYL series shrinkable label inserting machines



瓶身到底型 **FULL BODY LABELING TYPE**

瓶身中間定位型 **MIDDLE BODY LABELING TYPE**

整瓶型 **OVERALL BOTTLE TYPE**

瓶口型 **CAP SEALING TYPE**

背套型 **CAP LABEING TYPE**

旭源包裝科技股份有限公司

PVC PE PET PP OPS OPP BOPP 熱收縮膜(管、套、袋)
彩色印刷收縮商標／全自動套標籤機
食品／工業及其他複合軟性包裝

http://www.xuyuanpack.com
E-mail:info@xuyuanpack.com

TAIWAN HEADQUARTER AND MANUFACTURE PLANT
305046 新竹縣新埔鎮巨埔里3鄰新龍路98巷33弄10號
No.10, Aly. 33 ,Ln. 98, Xinlong Rd., 3rd Neighborhood, Jupu Vil. Xinpu Township, Hsinchu County 305046, Taiwan(R.O.C.)
TEL：+886-3-5982727 FAX：+886-3-5982738

CHIAYI Fab.
622011 嘉義縣大林鎮大美里大埔美園區二路7號
No.7, Yuanqu 2nd Rd., Dapumei, Damei Village, Dalin Township, Chiayi County 622011, Taiwan(R.O.C.)
TEL：+886-5-2952888 FAX：+886-5-2952999

INDONESIA Site Office
TEL : +62-21-89904402 (REP) FAX : +62-21-89908323

SHANGHAI Site Office
TEL : +86-21-36536830 (REP) FAX : +86-21-36536827

USA Site Office
TEL : +01-501-492-3893 (REP)

BRAZIL Site Office
TEL : +55-14-3845-1965 (REP)

INDIA Site Office
TEL : +91-97691-10133

Auto Splicer
自動接料機



XU YUAN PACKAGING TECHNOLOGY., LTD.

Auto Splicer

自動接料機

產品特性介紹

產品特性介紹

自動接料裝置配備2卷套筒和整合式堆積裝置，專為中高速設計，捲筒速度最高達120m/min。只需使用切割工具將套筒切割並放置在正確的位置，裝置即可自動拼接，將接料帶放置在套筒上，並將舊捲軸的末端與新捲軸的開頭連接起來。接料單元從一個捲軸移動到下一個捲軸時，整合的累積單元提供套筒，允許在接料更換期間持續生產，實現不停機生產。整個過程實現全自動化接料，操作員使用者友善，操作簡便。

特色

1. 支援 2 個標籤卷，（標籤高度 100 – 220mm）標籤寬度 170mm。
2. 無需使用者乾預的生產持續時間。
3. 自動拼接標籤卷，不減少產量。
4. 節省空間且符合人體工學的設計。
5. 每小時產量高達 36000 個容器。

Product Features

Product Features

Auto splicer is equipped with 2 reels of sleeve and integrated accumulation unit. Designed for mid to high-speeds. (web - speed max 120m/min).The sleeve only needs to be cut, by use of cutting tool and placed in correct position, then the will make an automatic splice, placing splice tape on sleeve and will make the connection between the end of reel and the begin of new reel. An integrated accumulation-unit provides sleeve when splice unit moves from one reel to next, which allows to continue production during splice change. Production not stopped, Prepare sleeve, Automatic splice, User friendly.

Characteristic

1. Supports two label reels, (label height of 100 –220 mm) Label width 170mm.
2. Production duration without user intervention.
3. Splices label reels automatically without any reduction in output.
4. Space-saving and ergonomic design.
5. Output of up to 36000 containers per hour.

